

PPC-P150-H

**15 inch TFT Touch Screen Embedded Industrial Panel PC powered by Intel Celeron J1900/
Core i5 4200U/i5 7200U/i7 7500U, 6 x COM, 2 x LAN, 4 x USB**



Product description:

PPC-P150-H is a touch panel computer solution designed for human-machine interface applications. It uses Intel® J1900 processor/Intel I5-4200U/I5-7200U/I7-7500U processor, onboard 2GB DDR3/4GB DDR3 memory, LCD with a resolution of 1024x768 and high-temperature full-screen capacitive touch screen. The whole machine adopts 9~36V DC power supply, which can effectively control the internal heat of the computer; provide a more diversified data storage device, support MSATA/SSD and SATA2.5" notebook hard disk at the same time; integrate a rich I/O interface, 6 x RS232 Or 4 x RS232/2 x 485, 2 x 10~1000M Ethernet ports and 2 x USB2.0, 2 x USB3.0 ports.

PPC-P150-H supports panel embedded installation and wall-mounted installation. It only needs 4 mounting clips to be tightened. Installation and maintenance are very convenient; the front panel meets the NEMA/IP65 waterproof and dustproof standard, which can effectively control the splash caused by the scene. Water droplets and water vapor enter the host and affect the normal operation of the equipment; the equipment adopts a fanless design, limited control of dust entering the equipment, ensuring a more stable operation of the equipment, and quickly dissipating the internal heat of the system through the external surface heat sink, so that it can adapt More harsh on-site environment; most suitable for application in factory automation, machinery manufacturing, numerical control equipment, textile equipment, intelligent power, food traceability and other host computer monitoring and control.

PPC-P150-H is compatible with mainstream operating systems and embedded operating systems such as Windows7, Windows10, Linux, etc. It can run application software and programs based on the above operating systems independently developed by customers, and install industrial automation configuration software to form a powerful man-machine interface.

Feature:

Using the latest technology to stamp the chassis, the shell is firm and the appearance is beautiful
15" true color LCD display, resolution 1024x768, backlight service life up to 50000 hours

The touch screen adopts a full-flat capacitive touch screen. The number of clicks can reach 50 million times

9~36V wide-voltage DC power input, meeting industrial site power supply

Support built-in 4G/WIFI and Bluetooth devices (optional)

Large-area aluminum fin active heat dissipation design ensures that the tablet can work uninterrupted in harsh industrial scenes

Specification:




PPC-P150-H

System parameters	CPU	J1900/I5-4200U/I5-7200U/I7-7500U processor
	RAM	Onboard 2GB DDR3/4GB DDR3 (expandable)
	Disk	Support MSATA / SSD and SATA2.5 "notebook hard drives
I/O interface	Network port	2 x Intel Gigabit Ethernet
	Audio	RTLALC662 audio controller, LINE-out port
	USB	2 x USB2.0, 2 x USB3.0
	Serial port	6 x RS232(2 can be set to RS485/RS422)
LCD screen	Display	15" TFT LED
	Resolution	1024x768
	Brightness	350cd/m2
	Contrast	800:1
	Maximum color	16M
Touch screen	Types of	Capacitive
	Click life	250 grams of strength, 50 million times
	Response time	<5ms
	Transmittance	above 90%
	High temperature test	85°C/1000hrs
	Constant temperature and humidity test	85°C/90%RH/1000hrs
Mechanism parameters	Panel cabinet	The case adopts cast aluminum mold
	Installation method	The panel is embedded, and it can be installed with the bracket by VESA
	Power input	9~36V DC power supply
	Hole Size	375x288mm
	Overall dimensions	390x300x50mm
	Power	20W
	Weight	3KG
Environmental parameters	Operating temperature	-20~60°C (Electronic disk)
	Storage temperature	-30~80°C
	Front panel protection	IP65 standard

Ordering Information:

Product number	Configuration
PPC-P150-H/J1900	J1900/Onboard4G/2 x RJ-45/4 x USB/4 x RS232+1 x RS485+1 x (RS232/422/485)/Optional 9-36V
PPC-P150-H/I5-4200U	I5-4200U/Onboard 4G/2 x RJ-45/4 x USB/4 x RS232+1 x RS485+1 x (RS232/422/485)/Optional 9-36V
PPC-P150-H/I5-7200U	I5-7200U/4G/2 x RJ-45/4 x USB/4 x RS232+2 x (RS232/422/485)/Optional 9-36V
PPC-P150-H/I7-7500U	I7-7500U/4G/2 x RJ-45/4 x USB/4 x RS232+2 x (RS232/422/485)/Optional 9-36V

Dimensions:



Contact:

Allen Dai / Sales Manager

Armortec Technology Limited

Email: allen.y.dai@armortec.net

Skype: allen.dai89

Tel: +86 150 1266 9595