

EPC-D469Z

Fanless Wall Mount Industrial Mini PC with Intel Celeron J1900 2.0GHz quad core processor with 2 GbE LAN supporting mSATA and WiFi, 3G module



Feature:

Fanless heat sink structure

All aluminum alloy chassis, compact structure, flexible installation

Adopt Intel® Celeron J1900 2.0GHz quad core processor

1 x Mini-PCIE slot, support WIFI, 3G module

2 x WGI211AT Gigabit Ethernet port, support Wake on Lan function

Rich I/O: 1 x DC input, 6 x COM, 1 x VGA, 1 x HDMI, 2 x Lan, 2 x Aduio, 4 x USB

Specification:

Model No.	EPC-D469Z	
Chassis	Color	Black
	Dimension	235mmx200mmx52mm (L x W x H)
	Structure	Full aluminum fanless radiating structure
	Material	Full aluminum alloy
	Installation	Desktop, embedded, wall mount installation
Motherboard	Model	M50_2L
	Processor	Integrated Intel® Celeron J1900 2.0GHz quad core processor
	Chipset	Based on Intel® SOC platform
Graphics	HD Graphics	Integrated Intel® HD Graphics, support DirectX 11.1, OpenGL 3.2, support synchronous/asynchronous display
	Resolution	1 x VGA, max support 2560x1600@60Hz 1 x HDMI, max support 1920x1080@60Hz
Storage	Memory	1 x SODIMM support 1600/1333MHz DDR3L/1.35V memory, max up to 8GB

	HDD	Support 1 x 2.5-inch HDD expansion
	CF	N/A
	SSD	Support 1 x MSATA SSD expansion
Audio	Audio	Integrated ALC662 6 channels Hi-Fi audio controller, support MIC, Line_out
Network	Ethernet	2 x WGI211AT Gigabit Ethernet port, support Wake on LAN, PXE
	WiFi	1 x Mini-PCIE slot, support WiFi, 3G module
I/O port	USB	2 x USB2.0, 2 x USB3.0
	Power Switch	1 x Power Switch
	LAN	1 x LAN (RTL8111E/F, Gigabit Ethernet)
	Display	1 x VGA, 1 x HDMI display output
	Serial Port	5 x RS232 serial port, COM3 support RS485/422
	Power In	1 x 12V DC IN Jack
	Antenna	2 x WIFI/3G SMA antenna (optional)
	Audio	2 x MIC, 2 x Line-out
Power Adaptor	Input	AC 110V ~ 220V
	Output	DC 12V 5A
Reliability	Operating Temp.	0°C~45°C
	Storage Temp.	-20°C~70°C
	Relative Humidity	5%-95%, no condensing
	Vibration	0.5g rms/5-500HZ/random/operating
Operate System	Support Windows 7, Windows 8, Windows XP, Linux OS	

Ordering Information

No.	Model	Processor	Memory	Storage	LAN	COM	USB	WIFI	Adaptor	OS
1	EPC-D465Z	4300U/1.90GHz	/	/	2 x WGI211AT	6	4	N/A	12V/5A	/
2	EPC-D469Z	J1900U/2.0GHz	/	/	2 x RTL8111E	6	4	N/A	12V/5A	/

Packing List

1	SATA data cable
2	Power cord 3P 180cm, China
3	Accessory screw bag



www.armortec.net

Professional industrial PC and network appliance designer and manufacturer.

Optional Accessories

1	Power cord 3P 180cm, USA
2	Power cord 3P 180cm, Europe
3	Power cord 3P 180cm, UK
4	Power cord 3P 180cm, Japan
5	Power cord 3P 180cm, India

Contact:

Allen Dai / Sales Manager

Armortec Technology Limited

Email: allen.y.dai@armortec.net

Skype: allen.dai89

Tel: +86 150 1266 9595