

EPC-K509Z

Abundant COM ports Embedded Industrial Computer with Quad Core Celeron J1900, 6 COM, 6 USB, Black Color



Feature:

Fanless heatsink structure

All aluminum chassis, compact structure and flexible installing

Support WIFI/3G module, providing onboard SIM expansion slot(Optional)

1 x VGA/1 x HDMI

Intel Celeron J1900 Bay Trail Quad Core 2.0 GHz

I/O Interfaces: 1 x 2P power input, 6xCOM,1xVGA, 1 x LAN, 1 x Audio, 5xUSB 2.0, 1 x USB 3.0, 1xHDMI

Specification:

EPC-K509Z

Chassis	Color	Black
	Dimension	214mm x 200mm x 52mm(L x W x H)
	Structure	Full aluminum fanless cooling structure
	Material	Full aluminum alloy
	Install	Desktop / embedded installation
Motherboard	Model	M56-D6E
	Processor	Integrated Intel® Celeron J1900 quad core 2.0GHz processor
	Chipset	Adopt Intel® Baytrail SOC platform
Graphics	HD Graphics	Integrated Intel® HD Graphics, support DirectX 11.1, OpenGL 3.2, support synchronous / asynchronous display.
	Resolution	1 x VGA, max support 2560x1600@60Hz 1 x HDMI, max support 1920x1080@60Hz
Storage	RAM	1 x SODIMM support 1600/1333MHz DDR3L/1.35V memory, max support 8GB
	HDD	Support 1 x 2.5 inch SATA HDD expansion
	CF	N/A
	SSD	Support 1 x MSATA SSD expansion
Audio	Audio	Integrated ALC662 6 channels Hi-Fi audio controller, support MIC, Line_out
Network	Ethernet	1 x RTL8111F Gigabit LAN port, support Wake On LAN, PXE
	WiFi	1 x Mini-PCIE slot, support WiFi, 3G module

I/O Port	USB	5 x USB2.0, 1 x USB3.0
	Power Switch	1 x Power Switch
	LAN	1 x RJ45 Gigabit Ethernet port
	Display	1 x VGA, 1 x HDMI display output
	Serial Port	6 x RS232 serial port, COM3 support RS485/422
	Power In	1 x 12V DC IN Jack
	Antenna	2 x WIFI/3G SMA antenna (optional)
	Audio	2 x MIC, 2 x Line-out
Power Adaptor	Input	AC 110V ~ 220V
	Output	DC 12V 5A
Reliability	Operating Temp.	0°C~45°C
	Storage Temp.	-20°C~70°C
	Relative Humidity	5%-95%, no condensing
	Vibration	0.5g rms/5-500HZ/random/operating
Operate System	Support Windows 7, Windows 8.1, Windows10, Windows XP, Linux OS	

Ordering Information

No.	Model	Processor	Memory	HDD	GPIO	LAN	COM	HDMI	VGA	USB2.0	USB3.0	SIM	power-input
1	EPC-K509Z	J1900/2.0GHz	N/A	N/A	N/A	1	6	1	1	5	1	N/A	DC 12V

Packing List

1	Power cord 3P 180cm, China
2	60W external adapter
3	Driver CD
4	Accessory screw bag

Optional Accessories

1	Power cord 3P 180cm, USA
2	Power cord 3P 180cm, Europe
3	Power cord 3P 180cm, UK
4	Power cord 3P 180cm, Japan
5	Power cord 3P 180cm, India

Contact:

Allen Dai / Sales Manager

Armortec Technology Limited

Email: allen.y.dai@armortec.net

Skype: allen.dai89

Tel: +86 150 1266 9595