

NAS-04-SK2P

Integrated Intel® Skylake-U 3855U Dual-Core Dual-Thread processor Dual LAN 4 Bay NAS Storage Server



Feature:

System fan cooling structure, sheet metal material

System fan cooling structure, sheet metal material

Integrate @Intel Skylake-U 3855U CPU (Skylake-U and Kabylake-U series CPU OPTIONAL)

Dual-Core Dual-Thread processor

Supports 4 x 2.5" or 3.5" SSD/HDD , 1x12025 fan

Support 1x mSATA SSD

Mini-ITX Main board structure

DDR4 SO-DIMM 2400MHz memory, Max support 16GB

Supports 2 RJ45 ports(on-board), Max 4 x RJ45 ports by changing USB ports

NAS system that can integrate computers, routers, and set-top boxes into one, replacing traditional cloud disks, computers, routers, and set-top boxes

The IO ports in the image might be different from the real product, please refer to the spec sheet for correct IO details.


Specification:

Model	NAS-04-SK2P	
Chassis	Material/structure	Sheet metal material, system fan cooling structure
	Color	Black/Wood grain
	Dimensions (L x W x H)	263×190×180mm
	Installation	Desktop
Motherboard	CPU	Integrated @Intel Skylake-U 3855U CPU Dual-Core
	System chip	SOC
	Display	Integrated Intel® 1x HDMI1.4 (Max: 3840 x 2160@30Hz)
	RAM	Support DDR4 SO-DIMM memory slot, Support 2400MHz memory, Max support 16GB
Front panel interface	Power	1 x Power switch
	Hard drive	4 x SATA hard disk
	USB	2x USB 2.0 port
	LED	Power LED*1, HDD LED*1, Power SW*1, Reset*1
Rear panel interface	Display interface	1 x HDMI1.4 port (Max: 3840 x 2160@30Hz)
	LAN	2 x I211AT Gigabit network card, support Wake on LAN/PXE function
	USB	2 x USB3.0 port
	COM	1x COM -RS232 Serial interface
	Audio	Realtek ALC662-VDO 1x Audio_out + 1x Mic_in
	PS/2	1 x PS/2 keyboard and mouse interface
	Power supply	1 x AC power connector, ATX power supply
Storage	SATA	4 x 2.5/3.5-inch hard disk
	SSD	1 x MSATA SSD expansion, SSD transmission speed up to 6Gbps
Software Support	Microsoft Windows	Windows7, 8.1, 10; Linux
	Watch Dog	Support hardware reset function (256 levels, 0~255 seconds)
Power requirements	Power type	Flex 1U power supply
	Voltage input	AC 110~220V

Dimensions:

Panel View

The IO ports in the image might be different from the real product, please refer to the spec sheet for correct IO details.



Ordering information

No.	Model	Processor	Memory	HDD	GPIO	LAN	COM	HDMI	VGA	USB2.0	USB3.0	PS/2	Power-input
1	NAS-04-SK2P (3855U)	3855U 1.60 GHz	1 x DDR4	N/A	N/A	2	1	1	1	2	2	1	ATX power supply

Contact:

Allen Dai / Sales Manager

Armortec Technology Limited

Email: allen.y.dai@armortec.net

Skype: allen.dai89

Tel: +86 150 1266 9595