

SS-212-C612D

2U Rackmount Storage Server powered by Intel® E5-2600 v3/v4, E5-1600 v3/v4 Processors with 12 x 3.5/2.5 inch HDD bay



Feature:

Intel® Xeon® processor E5-2600 v3/v4, E5-1600 v3/v4 family (up to 145W TDP) , Dual Socket R3 (LGA 2011)
 A highly scalable rackmount NAS to aptly accommodate large business needs for scalability, suitable for video post-production and massive surveillance deployment
 8 x 288-pin DDR4 DIMM slots, 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit , Up to 256GB DDR4 ECC RDIMM, Up to 512GB DDR4 ECC LRDIMM
 Elastic expandability with 1 x PCIe 3.0 x16 slots, 4 x PCI-E 3.0 x8 slot, 1 x PCI-E 2.0 x4 slot for installing additional expansion card

Overview:

The SS-212-C612D is a 12-bay compact 2U Rackmount storage server/NAS for large and extensive scaling of data storage. Its comprehensive data protection technologies, including High Availability, hybrid cloud backup, and server or virtual machine backup approaches, make it a reliable server for massive storage deployment. SS-212-C612D is backed by Armortec's 3 year limited warranty.

Specification:

SS-212-C612D

CPU	Intel® Xeon® processor E5-2600 v3/v4, E5-1600 v3/v4 family (up to 145W TDP) , Dual Socket R3 (LGA 2011)
Hardware encryption engine	Yes (AES-NI)
Memory	8 x 288-pin DDR4 DIMM slots, 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit, Up to 256GB DDR4 ECC RDIMM, Up to 512GB DDR4 ECC LRDIMM
Front drive type	12 x 3.5" or 2.5" SAS/SATA HDD/SSD (drives not included)
Hot swappable drive	Yes
Internal drive type	3 x 2.5" SATA HDD/SSD
External port	2 x USB 3.0 ports 4 x USB 2.0 ports
Dimensions (HxWxD)	88 x 437.5 x 650 mm
Weight	-
LAN	2 x RJ45 Gigabit Ethernet LAN ports



www.armortec.net

Professional industrial PC and network appliance designer and manufacturer.

Wake on LAN/WAN	Yes
BMC	Aspeed AST2400
PCIe 3.0 slot	1 x PCI-E 3.0 x16 slot 4 x PCI-E 3.0 x 8 slot 1 x PCI-E 2.0 x 4 slot High-performance network interface card support
Scheduled power on/off	Yes
System fan	4
Power supply	Standard 800W platinum server single power supply; optional 800W 1+1 redundant power supply; optional -48V DC power supply; support 240V high voltage DC power supply
Input power voltage	100~240V AC or 48V DC
System Control	1 x Reset button, 1 x UID SW, 1 x Power SW 1 x Power LED, 1 x HDD LED, 1 x NIC LED, 1 x UID LED 1 x OH/FAN Fail LED, 1 X Power Fail LED
Supported OS	Windows Server 2012/2008 Novell SLES 11 SP3 Red Hat Enterprise Linux 7.0 Ubuntu Server 14.04
Operating temperature	5°C to 35°C
Storage temperature	-40°C to 55°C
Relative humidity	Non operating, 0% to 95% RH
Maximum operating altitude	5,000 m (16,400 ft)

CPU Availability

1	Intel® Xeon® processor E5-2600 v3, E5-1600 v3 family (up to 145W TDP) , Dual Socket R3 (LGA 2011)
---	---

Contact:

Allen Dai / Sales Manager
 Armortec Technology Limited
 Email: allen.y.dai@armortec.net
 Skype: allen.dai89
 Tel: +86 150 1266 9595